



Emergency SAMCOM SLM 18 1x8W 30CM, mode: maintained, menggunakan lampu tipe fluorescent, durasi: 2~3 jam, tipe baterai: nickel cadminium cells

Description

Emergency SAMCOM SLM 18 1x8W 30CM, mode: maintained, menggunakan lampu tipe fluorescent, durasi: 2~3 jam, tipe baterai: nickel cadminium cells.

Produk dapat diandalkan sebagai lampu darurat petunjuk arah evakuasi cepat agar orang-orang menjauh dari ancaman atau kejadian yang sebenarnya dari bahaya.

Baca juga produk lampu serupa: Lampu Emergency EXIT Box TLD 1x10w.

Sangat ideal dipakai sebagai lampu untuk:

- lampu emergency untuk gedung shopping center
- sebagai penerangan tanda exit apartemen;
- banyak dipakai untuk area pabrik;
- cocok juga untuk exit gedung sekolah modern;
- penerangan emergency exit stasiun;
- dan berbagai kebutuhan lainnya sesuai fungsi dan kegunaan.

Spesifikasi produk emergency Samcom SLM 18 ini sebagai berikut:

1. INPUT VOLTAGE : 230Vac 50/60Hz ±10% or 115Vac 50/60Hz ±10% or others
2. BATTERY : 2.4V 2.5AH/4.5AH High temp rated Nickel Cadmium cells or others
3. LAMP USED : Fluorescent tube 1 x 8W daylight 30cm
4. RATED PERIOD : > 2 hrs, 3 hrs or others
5. MODE : Maintained
6. OPERATIONTEMPERATURE : ta 40 ºC
7. POWER CONSUMPTION : < 12VA
8. CHARGE MONITOR : Super bright green LED 5mm Ø
9. RECHARGE PERIOD : 16 ~ 24 hrs
10. EMERGENCY LUMINANCE : > 8 cd/m2
11. ELECTROMAGNETIC FIELD : 12.2m gause @ 0.1m
12. CHARGER : Hybrid controlled charger
13. PROTECTION : Low volt cut-off to prevent battery over discharge Incoming AC fuse and Battery DC fuse Tropical climate protection coating on hybrid control circuit
14. CONSTRUCTION : Electrode galvanised sheet steel with epoxy powder coating 20mm Ø K/O hole, Fire Retardant Acrylic Opal diffuser

15. DIMENSION : 420mm(L) x 75mm(W) x 298mm(H)
16. WEIGHT : 3.30kg (Net) / 3.40kg (Gross)
17. PACKING : One unit per carton
18. CARTON / DIMENSION : Double wall corrugated / 450mm(L) x 90mm(W) x 310mm(H)
19. COMPLIANCE : CP 19:2000, SS263 : Part 2, IEC 598-2-22
20. WARRANTY : 1 Year
21. ACCESSORY : Wall mounting bracket (for single face)