

Lampu SAMCOM SLED X2 Emergency fire retardant, menggunakan tipe baterai nickel cadmium, model single face (1sisi) & double face (2sisi)



Description

Lampu SAMCOM SLED X2 Emergency fire retardant, menggunakan tipe baterai nickel cadmium, model single face (1sisi) & double face (2sisi).

Lihat produk exit lainnya: Lampu Exit EXPLOSION Proof LED Terbaru.

Spesifikasi lampu exit Samcom ini sebagai berikut:

1. brand: Samcom
2. INPUT VOLTAGE : 220 ~ 240Vac 50/60Hz ± 10%, A: 0.019 Pf: 0.44
3. BATTERY : 3.6V 0.9Ah High temp rated Nickel Cadmium cells or others, 1.5Ah High temp rated Lithium Iron Phosphate
4. LAMP USED : SMT White LED strip > 30,000 hrs
5. RATED PERIOD : > 2 hrs or others
6. MODE : Maintained
7. OPERATION TEMPERATURE : ta 40 °C
8. POWER CONSUMPTION: 2.5 Watt
9. CHARGE MONITOR : Super bright Green LED 5mm Ø
10. RECHARGE PERIOD : 16 ~ 24 hrs
11. EMERGENCY LUMINANCE: > 8 cd/m2
12. ELECTROMAGNETIC FIELD: 17m gause @ 0.1m
13. CHARGER : Hybrid controlled charger
14. PROTECTION : Low volt cut-off to prevent battery over discharge, Incoming AC fuse and Battery DC fuse, Tropical climate protection coating on hybrid control circuit
15. CONSTRUCTION : Electrode galvanised sheet steel with epoxy powder coating, 20mm Ø K/O hole, Fire Retardant Acrylic diffuser
16. DIMENSION : 352mm(L) x 52(W) x 252mm(H)
17. WEIGHT : 1.25kg (Net) / 1.45kg (Gross)
18. CARTON / DIMENSION : Double wall corrugated / 415mm(L) x 70mm(W) x 295mm(H)
19. COMPLIANCE : EN IEC 61558-1:2019, SS263-2/A2: 2008, SS563-1:2010, SS563-2/A1:2013